■■■■ ΛCTIV

Asset Tag TGA

ACTIVE RFID



- Beacon tag transmitting a unique ID & data at pre-set intervals
- Ultra long-range transmitter
- Anti-tamper alert option
- Motion sensor option
- Ruggedised IP67 Industrialised Housing

The TGA Activ Asset IP67 Tag continuously transmits a unique ID number which can be detected by Wavetrend[®] reader. An internal battery powers the tag and Wavetrend's patented ultra low power use design ensures longer battery life at higher rates of transmission than any other brand of active RFID tag. Various preset transmission intervals are available.

KEY FEATURES	BUSINESS BENEFITS
The tag can be configured to hold standard 26-bit Wiegand numbering	Allows tag to be used with existing access control systems separately or together with the active RFID system.
Configurable settings include:	
■ Site/vendor ID	 A unique code that can be allocated by Wavetrend to each customer on request. Readers can be set to ignore tags with incorrect site codes.
■ Tag ID	• 4.2 billion tag ID's are available per site code.
■ Tag Age Counter	 The Age Counter allows for advance notification of the end of battery life and for the unique identification for each transmission made by the tag.
Various transmission repetition intervals	 Different status transmission intervals allow tags to be used in diverse applications while offering the best battery life spans in the market.
 Movement Alert 	 Provides instant notification of an attempt to move a tag through rapid alert transmissions for 5 seconds.
■ Tamper Alarm	 Provides instant notification of unauthorized attempts to remove a tag from an asset.
Collision avoidance algorithm	Reduces loss of data caused by simultaneous transmissions from multiple tags.
Ultra low power consumption	Typical lifespan of 3 years when transmitting at the standard or greater interval.
Sealed to IP67 standards	Waterproof

Best Usage Guide



Personne



Track Assets



Use on Metal



Indoor Use



Outdoor Use



IP67 Waterproof

© 2012 Wavetrend Europe Limited | All Rights Reserved | All specifications are subject to change without notice.

RFID | ACTIVATING YOUR BUSINESS

■■■ ΛCTIV

Asset Tag

ACTIVE RFID

Typical Applications

The TGA Asset Tag has a unique omni directional antenna design allowing the tag to be read from all directions and to be deployed equally well on metallic and non metallic assets.

Optimum read range is achieved on metal with a 10% reduction on Non metals.

The tag is sealed to IP67 providing the highest level of water ingress protection.

Model Range

The tags can be ordered using the part numbers listed below:

L-S	eries

TGA TGA-MS includes motion sensor

Air Interface Protocols

L-Series refers to proprietary communication protocol used between Wavetrend® tags and readers.

L-Series tags provide ultra long read range and are ideal for use in low tag density (< 30 tags per reader) operations such as personnel tracking, small asset management applications and access control systems.

Ordering & Further Information

For more information on purchasing the Activ TGA Tag please email Wavetrend's Sales team:

sales@wavetrend.net

For more information on Wavetrend® visit our website.

Specifications

Environmental Operating temperature Storage temperature Humidity	: -30°C to +60°C : -40°C to +70°C : 5% to 90% (non-condensing)
Physical Size Weight Colour Material	: 68 x 36 x 16mm : 25g : Black : Nylon
Radio Frequency Transmit Frequency	: 433.92 MHz
Range	: 1 to 100+ meters (actual range is determined by the choice of reader & antenna used to detect the tag and the environment it is used in)
Electrical Power	: Internally powered by lithium battery
Accessories	: Tag attachment kit
TA-TGA TA-TGA-AT	: Tag attachment kit : Tamper alerting tag attachment kit
TATONAL	(All sold in packs of 10)

* (from front page) Battery life calculations assume operation at room temperature with the default status transmission interval of 1.5 seconds, without the anti-tamper circuit armed and without a motion sensor fitted.

IMPORTANT NOTICE: Wavetrend ACTIV tags do not comply with the FCC Part 15 rules or hold IC approval, so are not available for sale into the United States of America or Canada.







Wavetrend and the Wavetrend logo are either registered trademarks or trademarks of Wavetrend Technologies Limited in the United States and/or other countries. All other trademarks are the property of their respective owners. The product(s) described in this document are protected by various patents held by Wavetrend. Refer to the URL www.wavetrend.net/IPR for information on all patents and trademarks held, and for Wavetrend's Policy on Intellectual Property Rights.

© 2012 Wavetrend Europe Limited | All Rights Reserved | All specifications are subject to change without notice.

WWW.WAVETREND.NET